



LPG for butane

Item	Component	Unit	Min	Maximum	Test methods
1	Sp.gr. @60	-	0.56	0.60	Astm D 2598
2	Methane	Ppm	-	Nil	Astm D 2163
3	Ethane	Vol%	-	0.08	Astm D 2163
4	Propane	Vol%	-	2	Astm D 2163
5	Butanes	Vol%	97.0	-	Astm D 2163
6	Pentanes & heavier	Vol%	-	1.0	Astm D 2163
7	Vapor pressure @100 if	Psig	-	70	Astm D 1267 Astm D 2598
8	Corrosion (copper strip)	-	-	No.1 strip	Astm D 1838,5453
G	Total sulfur	Ppmw	-	30	Astm D 1266,2784
10	Hydrogen sulfide	Ppmv	-	Negative (<4 ppmv)	Astm D 2420
11	Water content	Ppmw	-	10	Astm D1744, 2713
12	Free water	-	-	None	Visual
13	Residues 1) Residue number 2) Oil number	Ppmw	-	0.05	Astm D 2158

ADDRESS: No61-Ofogh Building – Farahzadi Blvd – Tehran-Iran

Tell: +98 21 22132058 ,

WhatsApp: +98 930 517 7388

Email: info@saltakoil.com

Website: www.saltakoil.com



LPG for propane

Item	Component	Unit	Minimu	Maximum	Test Methods
1	Sp.gr. @60	-	0.48	0.52	ASTM D 2598
2	Methane	ppmv	-	NIL	ASTM D 2163
3	Ethane	Vol %	-	2.0	ASTM D 2163
4	Propane	Vol %	96	-	ASTM D 2163
5	Butanes	Vol %	-	2.0	ASTM D 2163
6	Pentanes & Heavier	Vol %	-	0.05	ASTM D 2163
7	Vapor pressure @100 °F	psig	-	200	ASTM D 1267 ASTM D 2598
8	Corrosion (copper strip)	-	-	No.1 strip	ASTM D 1838
9	Total sulfur	ppmw	-	30	ASTM D 1266,2784
10	Hydrogen sulfide	ppmv	-	Negative (<4 ppmv)	ASTM D 2420
11	Water Content	ppmw	-	Pass (<10 ppmw)	ASTM D 2713
12	Residue 1-Residue number 2- Oil number	ppmw	-	0.05	ASTM D 2158

ADDRESS: No61-Ofogh Building – Farahzadi Blvd – Tehran-Iran

Tell: +98 21 22132058

WhatsApp: +98 930 517 7388

Email: info@saltakoil.com

Website: www.saltakoil.com



SALTAK OIL COMPANY

LPG

Item	Component	Unit	Minimum	Maximum	Test Methods
1	Sp.gr. @60			(k)	ASTM D 2598
2	Methane	ppmv	-	NIL	ASTM D 2163
3	Ethane	Vol%	-	1	ASTM D 2163
4	Propane	Vol%	97 C)		ASTM D 2163
5	Butanes	Vol%			ASTM D 2163
6	Pentanes & Heavier	Vol%	-	2	ASTM D 2163
7	Vapor pressure @100 IT	psig	(k)		ASTM D 1267 ASTM D 2598
8	Corrosion (copper strip)		-	No.1 strip	ASTM D 1838,5453
g	Total sulfur	ppmw	-	30	ASTM D 1266,2784
10	Hydrogen sulfide	ppmv	-	Negative (<4 ppmv)	ASTM D 2420
11	Water Content	ppmw	-	10	ASTM D1744, 2713
12	Free Water		-	None	Visual
13	Residues 1) Residue number 2) Oil number	ppmw	-	0.05	ASTM D 2158

ADDRESS: No61-Ofogh Building – Farahzadi Blvd – Tehran-Iran

Tell: +98 21 22132058 ,

WhatsApp: +98 930 517 7388

Email: info@saltakoil.com

Website: www.saltakoil.com